

# Additional Standard Features and Equipment

## ELECTRICAL

- 4 Maintenance-Free Deep-Cycle, House Batteries on Slide-Out Tray
- Heart Interface Inverter/Converter (Battery Charger)
- 12VDC Circuit Breaker Panel
- 110 VAC Distribution Circuit Breaker Control Panel
- 12 VDC Chassis Circuit Breaker Panel
- Battery Fuse Link (250 Amp)
- Battery Cutoff Switches

## ENTRY AREA

- Automatic Two-Step Entry
- Large Entry Light
- Illuminated Entry Handle
- Illuminated Door Bell
- Exterior Speakers

## WINDSHIELD AREA

- Fully Tinted Windshield
- Dual Motor Intermittent Windshield Wipers w/Washer
- Power Adjusted, Heated Driving Mirrors w/Turn Signal

## LIGHTS

- Clearance Lights
- Sealed Beam Docking Lights
- Quartz Halogen
  - Driving Lights
  - Headlights
  - Fog Lights
- Remote Control Spot/Flood Light

## ROOF

- TV Antenna
- 2 - Low Profile Air Conditioners
- Dual Air Horns
- Dual CB Antennas

## STORAGE

- Lighted/Vented/Lined Storage Compartments
- Pass-Through Cargo Area
- GFI Protected 110V Receptacle
- Single Handle Paddle Latch w/Lock

## DUMP VALVE COMPARTMENT

- Sewer Hose
- Dump Station w/Gray & Black Water Valves
- Fresh Water Fill

## UTILITY BOX

- Lighted, Easy Access for Exterior Power Hook-Ups
- TV & Telephone Cable Hook-Ups
- 50 Amp External Power Connector

## OTHER

- Dual Fuel Fill
- High Strength Composite Bumpers
- Custom Anodized Aluminum Grills
- Mud Flaps; Front & Rear
- Fully Shrouded Fiberglass Inner Wheel Wells
- Color-Coordinated Patio & Window Awnings
- Full Automotive Undercoating
- Trailer Hitch, Mount & Connector
- 7.5 Onan Diesel Generator
- Four Point Heavy-Duty Hydraulic Levelers

## POWER TRAIN

- Caterpillar 3176 Turbocharged Diesel Engine
  - Air-to-Air AfterCooling (ATAAC)
  - 1225 lb-ft Torque @ 1300 RPM
  - 51% Torque Rise
  - 325 b.h.p. @ 2100 RPM
- Boost Start System w/Continuous Duty Solenoid
- Allison HT 747 4-Speed Automatic Transmission
- 12 Volt, 160 Amp Alternator
- Heavy-Duty Transmission Cooler
- Electric Transmission Range Selector
- Electronic Cruise Control
- Engine Preheat for Cold Weather Starting

## CHASSIS

- Custom Gillig Chassis
- Tires & Wheels
  - 11R x 22.5 Radial Tires
  - Load Range G
  - Four Alcoa Aluminum and Two Steel Wheels
- Front Suspension
  - Gillig Proprietary Air Ride
  - Two Heavy Duty Koni Shock Absorbers
  - Anti Sway Bar
- Rear Suspension
  - RideWell Suspension System with Four Outboard Air Bags
  - Four Heavy-Duty Koni Shock Absorbers
- TRW-Ross Integral Power Steering w/Tilt Telescoping Steering Column
- Dual Air Brake System
- Two Heavy-Duty 12V, 8D Chassis Batteries on Slide-Out Tray



### VEHICLE WEIGHT RATINGS

40' - Caterpillar Engine 3176/325 b.h.p.  
G.C.W.R.: 36,540 lbs. / G.V.W.R.: 33,540 lbs.  
Front Axle: 13,220 lbs / Rear Axle: 20,320 lbs.  
Approx. Curb Weight (Fuel Only): 40' = 29,400 lbs.

Due to constant product improvements, Beaver Coaches Inc., reserves the right to make changes at any time without notice in prices and specifications.

## LIMITED WARRANTY

Beaver's coaches come with a one year limited warranty. The limited warranty is set out in full in Beaver's Owner's Manual. Please refer to the owner's manual for a complete description of Beaver's one year limited warranty and for a description of the exceptions and exclusions to that warranty. Certain component parts are warranted by the component part manufacturer rather than Beaver including the engine, transmission and chassis. With respect to those components, please refer to each manufacturer's Statement of Warranty for the most current information. A copy of Beaver's Owner's Manual and its one year limited warranty is available from Beaver or the dealer upon request. Beaver encourages you to review the limited warranties prior to purchasing a coach.

For Additional Information Contact: